



Main Features

- ♦ PowerDigiS digital signage system
- ♦ Pre-defined signage content triggered by facial analytics
- ♦ Electronic Shelf Label changes dynamically based on gender/age
- ♦ Self-contained device for easy deployment

Product Overview

Instant Digital Shelf Solution includes PDSB 325, NDiS B535, 1080p camera, ESL base station, 2" ESL x 1, 4.4" ESL x 1, facial analytics software, and PowerDigiS signage software. High-definition camera is used to capture face characteristic of audience and send the data to NDiS B535 for further analysis and result gender/age data. Relevant signage content will be triggered based on the analysis result. Retailers can use electronic shelf labels to keep product information up to date and make minute-by-minute pricing changes.

Specifications

ESL solution system

- ♦ 2" ESL x 1
- ♦ 4.4" ESL x 1
- ♦ ESL Base station x 1
- ♦ ESL management system

- ♦ 4 x USB 3.0
- ♦ 4 x DB9 for RS-232
- ♦ 3 x HDMI 2.0
- ♦ 2 x RJ45 with LED for 10/100/1000Mbs Ethernet
- ♦ 1 x Mic-in/1 x Line-out

FHD Camera

- ♦ Full HD video recording (up to 1920 x 1080 pixels)
- ♦ H.264 video compression
- ♦ Built-in dual stereo mics with automatic noise reduction
- ♦ Automatic low-light correction

I/O Interface (PDSB 325)

- ♦ 1 x 19V DC in
- ♦ 2 x USB 2.0
- ♦ 4 x USB 3.0
- ♦ 1 x DB9 for RS-232
- ♦ 1 x VGA
- ♦ 1 x HDMI (4K resolution)
- ♦ 1 x RJ45 with LEDs for 10/100/1000Mbps Ethernet
- ♦ 1 x Mic-in/1 x Line-out

PC System (NDiS B535)

- ♦ 6th generation Intel® Core™ i5
- ♦ 500G HDD storage
- ♦ 4G DDR4 SO-DIMM
- ♦ Windows 8.1 operation system
- ♦ Facial analysis system
- ♦ ESL management system

Signage Display

- ♦ 8" TFT LCD monitor x 1
- ♦ Resolution 1024 x 768
- ♦ Brightness 250 nits

Dimensions

- ♦ 900mm (L) x 570mm (W) x 270mm (D)

Weight

- ♦ 32Kg

Ordering Information

• IDS-100

Instant Digital Shelf Solution, PDSB 325, NDiS B535, 1080p camera, ESL base station, 2" ESL x 1, 4.4" ESL x 1, facial analytics software, PowerDigiS signage software

Block Diagram

