

APPC 1240T

12.1" TFT SVGA 4:3 Flush Panel PC with Intel® Celeron® J1900, up to 2.42GHz,
Touch Screen, 4GB DDR3L, 3 x USB, 2 x COM



Main Features

- ♦ 4:3 12.1" SVGA fanless LED panel computer
- ♦ Intel® Celeron® J1900, Quad Core, low consumption CPU
- ♦ Flush panel by 5-wire touch screen
- ♦ Dual GbE/2nd display-VGA/Line-out/PS2 KB/MS
- ♦ 3 x USB/2 x mini-PCIe sockets/1 x CFast/2 x RS232/422/485
- ♦ DDR3L 4GB/2.5" HDD bracket
- ♦ IP65 compliant front panel
- ♦ Support JMobile HMI and CODESYS SoftLogic (optional)
- ♦ Mounting support: panel/wall/stand/VESA 100mm x 100mm
- ♦ Wide range power input 12V~30VDC

Product Overview

The 12.1" fanless panel PC APPC 1240T incorporating an industrial motherboard is intended for versatile industrial applications. APPC 1240T has a touch screen LED backlight LCD panel with 800 x 600 (SVGA) resolution and 450-nit brightness. The front panel which adopts flush design and complies with IP65 standard makes it the perfect fit in industrial applications.

This APPC series supports WWAN/WLAN expansion and others via dual Gigabit Ethernet connectors, two mini-PCIe slots and one SIM card holder. With support for wide power input of 12~30VDC, this APPC series can gain a strong foothold in industrial field and machine devices. In addition, this APPC series can hook 2nd display via a VGA port for dual independent display. APPC 1240T has two isolated RS232/422/485 ports.

Specifications

Panel

- ♦ LCD size: 12.1", 4:3
- ♦ Resolution: SVGA 800 x 600
- ♦ Luminance: 450cd/m²
- ♦ Contrast ratio: 700
- ♦ LCD color: 16.2M
- ♦ Viewing angle: 65 (U), 75 (D), 80 (L), 80 (R)
- ♦ Backlight: LED

Touch Screen

- ♦ 5-wire resistive (flush panel type)
- ♦ Light transmission: 80%
- ♦ Interface: USB

System

- ♦ CPU: on-board Intel® Celeron® Quad Core processor J1900 processor, up to 2.42GHz, 2M L2 cache
- ♦ BIOS: AMI BIOS
- ♦ System memory: 2 x 204-pin DDR3L SO-DIMM socket, 4GB DDR3L (default), support up to 8GB DDR3L-1066/1333, non-ECC and un-buffered
- ♦ Storage device:
 - 1 x external locked CFast socket
 - 1 x hard drive bay: optional 1 x 2.5" SATA HDD or 1 x SATA DOM

- ♦ Watchdog timer: Watchdog timeout can be programmable by software from 1 second to 255 seconds and from 1 minute to 255 minutes (tolerance 15% under room temperature 25°C)
- ♦ H/W status monitor: monitoring system temperature, and voltage
- ♦ Expansion: 2 x mini-PCIe sockets (support optional Wi-Fi, 3.5G module)

Rear I/O

- ♦ Ethernet: 2 x RJ45
- ♦ 2nd display VGA port: 1 x DB15
- ♦ Audio port: 1 x Line-out
- ♦ USB: 2 x USB 2.0, 1 x USB 3.0
- ♦ PS2 keyboard/mouse
- ♦ Power switch
- ♦ Reset button
- ♦ 2-pin remote power on/off switch
- ♦ COM #1: RS232/422/485 w/ 2.5kv isolated
- ♦ COM #2: RS232/422/485 w/ 2.5kv isolated


Audio

- ♦ HD audio codec: realtek ALC886-GR
- ♦ Audio interface: Line-out

Ethernet

- ♦ LAN chip: dual Intel® I210AT Gigabit LAN
- ♦ Ethernet interface: 10/100/1000 Base-Tx Ethernet compatible

Dimension Drawing



Mechanical & Environment

- Color: Pantone black\RAL 15 00 front bezel w/ Pantone 400C\RAL 090 80 10 metal style membrane
- IP protection: IP65 front
- Mounting: panel/wall/stand/VESA 100mm x 100mm
- Power input: 12V~30VDC
- Power adapter: optional AC to DC power adapter (+12V, 60W)
- Vibration:
 - IEC 68 2-64 (w/ HDD)
 - 1Grms @ sine, 5~500Hz, 1hr/axis (HDD operating)
 - 2Grms @ sine, 5~500Hz, 1hr/axis (CFast operating)
 - 2.2Grms @ random condition, 5~500Hz, 0.5hr/axis (non-operating)
- Shock:
 - IEC 68 2-27
 - HDD: 20G@wall mount, half sine, 11ms
- Operating temperature: -5°C to 60°C
- Storage temperature: -20°C to 75°C
- Operating humidity: 10%~90% relative humidity, non-condensing
Limits to be at 90% RH at max 50°C
- Dimension: 317 x 243 x 65.89mm
- Weight: 4 Kg

Certifications

- CE approval
- FCC Class A

OS Support Lists

- Windows 8 32-bit/64-bit
- Windows 7 32-bit/64-bit
- WinCE 7.0

Ordering Information

Barebone

- **APPC 1240T-J1900-4G (P/N: 10IA1240T07X0)**
12.1" SVGA LED backlight touch panel PC, Celeron® J1900 up to 2.42GHz, touch screen, 4GB DDR3L, 2 xRS232/422/485, brightness adjustment buttons

Options

- **12V, 60W AC/DC power adapter w/o power cord (P/N: 7400060031X00)**