



Main Features

- ♦ Dual Intel® Xeon® Scalable processor (LGA3647)
- ♦ 16 x DDR4-2666 RDIMM
- ♦ 2 x 2.5" swappable SSD/HDD
- ♦ 2 x Management ports
- ♦ 8 x LAN modules
- ♦ Supports Intel® QAT
- ♦ Redundant power supply
- ♦ Supports IPMI 2.0 remote management
- ♦ Intel® Select Solution for NFVI, VCDN (RHEL), and NFVI FP

Product Overview

The NSA 7146 is a 2U rackmount high-performance security appliance intended for more secure workloads and lower energy consumption in contributing to a greener world. Based on the Intel® Xeon® product family (codenamed Skylake-SP), NEXCOM's NSA 7146 features enhancements of in multi-core computing performance, flexible I/O throughput and interface, and Intel® QAT hardware acceleration technology to process network traffic for both enterprise and telecommunication applications.

Specifications

Main Board

- ♦ Dual Intel® Xeon® Skylake-SP Scalable processor (LGA3647), up to 165W
- ♦ Supports 2 x UPI between CPUs
- ♦ Intel® C627 w/ Intel® QAT
- ♦ Supports IPMI 2.0
- ♦ Supports Dual BIOS

Main Memory

- ♦ 16 x DDR4 2133/2400/2666 RDIMM sockets, up to 512GB

Storage

- ♦ 2 x 2.5" swappable SSD/HDD
- ♦ 1 x CFast

Interface External

- ♦ Button: power & reset
- ♦ LED: power/HDD/GPIO/system
- ♦ 2 x 2.5" swappable SSD/HDD bays
- ♦ 2 x USB 3.0 ports
- ♦ 2 x USB 2.0
- ♦ 1 x RJ45 type console
- ♦ 8 x PCIe x8 LAN module slots
- ♦ 2 x Management ports
- ♦ 1 x VGA port

- ♦ 3 x Swappable smart fans
- ♦ 2 x Power inlets
- ♦ LCM module

Interface Internal

- ♦ TPM 1.2/2.0 module (optional)

Power

- ♦ 700W 1+1 CRPS redundant power supply

Dimensions and Weight

- ♦ Chassis dimension: 440.6 mm x 570 mm x 88 mm
- ♦ Carton dimension: 774 mm x 636 mm x 293 mm
- ♦ Without packing: 19 kg
- ♦ With packing: 25 kg

Environment

- ♦ Operating temperature: 0°C~40°C
- ♦ Storage temperature: -20°C~75°C
- ♦ Relative humidity: 10%~90%, non-condensing

Certifications

- ♦ CE/FCC Class A
- ♦ UL

Ordering Information

Barebone

♦ NSA 7146 (P/N: 10S00714600X0)

2U w/ Dual Intel® Xeon® Scalable Processor, w/ QAT, IPMI, LCM and 8 x LAN modules

Model	P/N Controller	Interface	Type	Port Number	Bypass/Segment	Expansion Slot	Location Slot
NX 140F	10S20140F01X0	XL710-BM1	PCIe x8	4 SFP+	None	None	All Slot
NX 120F	10S20120F00X0	X710-BM2	PCIe x8	2 SFP+	None	None	All Slot
NI 140F	10SK000NI02X0	I350-AM4x1	PCIe x8	4 SFP	None	None	All Slot
NI 180F	10S10180F01X0	I350-AM4x2	PCIe x8	8 SFP	None	None	All Slot
NI 180C	10S10180C01X0	I350-AM4x2	PCIe x8	8 Copper	None	None	All Slot
NI 140C	10S10140C01X0	I350-AM4x1	PCIe x8	4 Copper	None	None	All Slot
NV 120F	10S50120F01X0	XXV710-AM2	PCIe x8	2 SPF28	None	None	All Slot
NQ 120F	10S40120F04X0	XL710-BM2	PCIe x8	2 QSFP+	None	None	All Slot
NC 120FIS4-OS	10S30012001X0	E810-CAM2	PCIe x16	2 QSFP28	None	None	All Slot

