

TCA 5170B

1U Rackmount uCPE w/ Intel® Xeon® Skylake-D SoC Processor,
8 x GbE RJ45, 4 x 10GbE Fiber and 2 x LAN Modules



Main Features

- Intel® Xeon® D-2177NT SoC, BGA type
- 8 x DDR4-2666 RDIMM
- 1 x 2.5 SSD, 1 x M.2 2280
- 8 x GbE RJ45 & 4 x 10GbE fiber
- 2 x LAN modules
- Supports Intel® QAT
- Redundant power supply
- Intel® Select Solution for uCPE (Ubuntu & CentOS)

Product Overview

The 1U rackmount uCPE TCA 5170B helps telecom companies build virtualization environments based on Intel®'s Xeon® Skylake-D SoC. Packing excellent multi-core CPU performance, accelerated data cryptography with Intel® QAT technology, and server-grade LAN functions into a small form factor, this 1U rackmount uCPE, an Intel® Select Solution for uCPE, creates virtualized environments for flexible VNF deployments in enterprises and branch offices.

Specifications

Main Board

- Intel® Xeon® Skylake-D SoC, BGA type
 - D-2177NT, 14 cores w/ QAT

Main Memory

- 8 x DDR4 2666 RDIMM sockets, up to 256GB

Storage Device

- 1 x 2.5" internal SSD/HDD bay
- 1 x M.2 2280 M key, supports SATA and PCIe x4 signal

Interface-External

- Button: Power & Reset
- LED: Power/HDD/2 x GPIO
- 1 x USB 3.0 port
- 1 x Micro USB type console
- 8 x GbE RJ45 ports
 - 2 x LAN bypass pairs
- 4 x 10GbE fiber ports
- 2 x PCIe x8 LAN module slots
- 1 x Management port
- 4 x SMA connectors for antennas
- 3 x Fixed smart fans
- 2 x Power inlets
- LCM module

Interface-Internal

- 1 x M.2 2230 E key
- 1 x M.2 3042 B key with SIM slot

Power

- 450W 1+1 redundant power supply

Dimensions and Weight

- Chassis dimension (mm): 438 x 480 x 44
- Package dimension(mm): 632 x 567 x 203
- Without packing: 8kg
- With packing: 12kg

Environment

- Operating temperature: 0°C~40°C
- Storage temperature: -20°C~80°C
- Relative humidity: 10%~90%, non-condensing

Certifications

- CE/FCC Class A

Ordering Information

♦ TCA 5170B (P/N: 10CA0517002X0)

1U Intel® Xeon® D-2177NT w/ QAT, w/ 4 x 10GbE & 8 x 1GbE LAN ports,
2 LAN module slots, w/ LCM

Model	P/N Controller	Interface	Type	Port Number	Bypass/ Segment	Expansion Slot	Location Slot
NX 140F	10S20140F01X0	XL710-BM1	PCIe x8	4 SFP+	None	None	All Slot
NX 142F	10S20142F01X0	XL710-BM1	PCIe x8	4 SFP+	2 bypass	None	All Slot
NX 142F-LR	10S20142F03X0	XL710-BM1	PCIe x8	4 SFP+	2 bypass	None	All Slot
NX 120F	10S20120F00X0	X710-BM2	PCIe x8	2 SFP+	None	None	All Slot
NI 140F	10SK000NI02X0	i350AM4x1	PCIe x8	4 SFP	None	None	All Slot
NI 180F	10S10180F01X0	i350AM4x2	PCIe x8	8 SFP	None	None	All Slot
NI 142C	10SK000NI03X0	i350AM4x1	PCIe x8	4 Copper	2 bypass	None	All Slot
NI 180C	10S10180C01X0	i350AM4x2	PCIe x8	8 Copper	None	None	All Slot
NI 184C	10S10184C01X0	i350AM4x2	PCIe x8	8 Copper	4 bypass	None	All Slot
NI 142F	10S10142F01X0	i350AM4x1	PCIe x8	4 SFP	2 bypass	None	All Slot
NI 121F	10S10121F01X0	i350AM2x1	PCIe x8	2 SFP	1 bypass	None	All Slot
NI 140C	10S10140C01X0	i350AM4x1	PCIe x8	4 Copper	None	None	All Slot
NV 120F	10S50120F01X0	XXV710-AM2	PCIe x8	2 SPF28	None	None	All Slot