



## Main Features

- 1U up workstation rack mount system
- Intel® 6th Xeon®/Core™/Pentium® processor
- Support DDR4 2400
- Four LAN module slots
- Support LCM module

## Product Overview

NEXCOM security hardware NSA 5170C helps small and medium-sized businesses (SMBs) scrutinize network traffic with ease. Featuring Intel® Xeon® E series product family, the NSA 5170C delivers scalable computing performance, high port density, and easy expansions of high-speed networking interface. By simplifying deployment, configuration, and management of network security controls, NEXCOM security hardware can fend off unauthorized access, patch potential security loopholes, and create protected networks for business environments.

## Specifications

### Main Board

- NSB 5170C
- Intel® 6th Gen. Xeon®/Core™/Pentium® processors
- Intel® C236

### Main Memory

- 4 x DDR4 2133 memory DIMM support ECC/non-ECC memory, max. 64GB

### LAN Features

- Swappable LAN modules
- Support Intel® i350/Intel® XL710 copper/fiber ports
- Support 10/100/1000/10G link speed
- LAN bypass

\* Please see LAN module list information

### I/O Interface-Front

- Power status/HDD status/2 x GPIO status LEDs
- 2 x Management ports (LAN chip: Intel® i210)
- 2 x USB 2.0 ports
- 1 x RJ45 type console port
- 1 x Reset button
- 4 x PCIe Gen.3 LAN module slots (x8, x8, x4, x4)

### I/O Interface-Rear

- 1 x VGA port
- 1 x Power button switch (optional)
- 1 x USB 2.0 port (optional)

### Devices

- 1 x CF card
- 1 x 2.5" HDD bay

### Power Input

- Power supply 220W (1+1) redundant PSU

### Dimensions

- Chassis dimension: 438 mm x 480 mm x 44 mm
- Carton dimension: TBC

### Weight

- Without packing: TBC
- With packing: TBC

### Certifications

- CE Approval
- FCC Class A
- UL

## Ordering Information

### Barebone

#### ◆ NSA 5170C (P/N: 10S00517002X0)

Supports Intel® 6th Gen. Xeon®/Core™/Pentium® processors, 4 x DDR4 memory slots, 2 x PCIe GbE LAN ports, CF card socket, USB ports, VGA port, 2 x PCIe x8 LAN and 2 x PCIe x4 LAN expansion slot (front), w/o LCM

Model	P/N Controller	Interface	Type	Port Number	Bypass/Segment	Expansion Slot	Location Slot
NX 140F	10S20140F01X0	XL710-BM1	PCIe x8	4 SFP+	None	None	1,2
NX 142F	10S20142F01X0	XL710-BM1	PCIe x8	4 SFP+	2 bypass	None	1,2
NX 120F	10S20120F00X0	X710-BM2	PCIe x8	2 SFP+	None	None	1,2
NI 140F	10SK000NI02X0	i350AM4x1	PCIe x8	4 SFP	None	None	All Slot
NI 180F	10S10180F01X0	i350AM4x2	PCIe x8	8 SFP	None	None	2
NI 142C	10SK000NI03X0	i350AM4x1	PCIe x8	4 Copper	2 bypass	None	All Slot
NI 180C	10S10180C01X0	i350AM4x2	PCIe x8	8 Copper	None	None	2
NI 184C	10S10184C01X0	i350AM4x2	PCIe x8	8 Copper	4 bypass	None	2
NI 142F	10S10142F01X0	i350AM4x1	PCIe x8	4 SFP	2 bypass	None	All Slot
NI 121F	10S10121F01X0	i350AM2x1	PCIe x8	2 SFP	1 bypass	None	All Slot
NI 140C	10S10140C01X0	i350AM4x1	PCIe x8	4 Copper	None	None	All Slot
NC220Q28M	10S30022002X0	MT27708A0-FDCF-CE	PCIe x16	2 QSFP28	None	None	1,2

