



Main Features

- Support Multiple IO Interface
- Wide Range DC input from 9~36V
- Support RAM Mount Kit
- External Antenna connector for GPS or WWAN module

Specifications

I/O Ports

- 1 x DB9 with Ethernet LAN x1 & USB x2 Port
- 1 x DB15 VGA
- 1 x DB9 RS-232
- 1 x 32-pin PoGo connector
- 1 x SMA-type GPS antenna connector
- 1 x SMA-type WWAN antenna connector
- 1 x 9~36VDC power input

Indication LED

- Power on LED Blue
- LAN Link LED Green
- LAN Access LED Yellow

Dimension

- 230mm x 282mm x 71mm
- Weight : 1.95Kg

Construction

- Plastic ABS+PC
- Metal SECC

Environment

- Operating temperature : -20°C to 50°C
- Relative humidity : 5% to 95% non-condensing
- Vibration : 5G with MRC 1000 with SSD
- Shock : 30G with MRC 1000 with SSD

Rugged Grade

- IP54
- Compliance with MIL-STD-810F

Certifications

- CE approval
- FCC class B

Ordering Information

- **MTK 10-VMC (P/N : 10UK10VMC00X0)**
Vehicle docking station with USB/VGA/RS232/LAN

Optional Accessories

Part No.	Description
60233VGA32X00	Vehicle Dock USB/Ethernet adapter cable
60233PW231X00	Vehicle Dock Bare Wire Power Cable
60233PW232X00	12V to 12V Vehicle Power Cable (cigarette adapter)

