

VTC Series Accessories

VTK 61B



Main Features

- ♦ Back up smart battery + charger
- ♦ Thermal control
- ♦ SMBus interface
- ♦ For VTC 6xxx series

Specifications

Back up smart battery + Charger

- ♦ Battery back-up for 4 hours in system full loading (1.4A/12V)
- ♦ Battery status is detectable by S/W
- ♦ 2 x LED indicators for the battery status
- ♦ Input voltage : 6-36V with ignition control
- ♦ Output voltage : 12V with ignition for VTC Series System

Operation Temperature

- ♦ 0°C to +55°C

Certification

- ♦ CE approval
- ♦ FCC

Dimensions

- ♦ 238mm (W) x 150mm (L) x 25mm (H)
- ♦ 1.75 Kg (3.86 Lb)

Ordering Information

- ♦ VTK 61B (P/N : 10VK0061B00X0)
- ♦ VTK 61B1 (P/N : 10VK0061B02X0, for VTC1000 only)

VTK 61P



Main Features

- ♦ IP65 compliant, anti-dust & anti-water protection kit
- ♦ Cables and antennas can be connected on VTC 6000 with external peripheral devices
- ♦ LED status is readable through window
- ♦ VTK 61P designed for VTC 6100/VTC 6110/VTC 6120/VTC 6200-NI
- ♦ Available on customization for VTC71xx-Bx series

Specifications

Dimensions

- ♦ 260mm (L) x 306mm (W) x 50mm (H)
- ♦ 2.8 Kg (6.18 Lb)

Ordering Information

- ♦ VTK 61P (P/N : 10VK0061P00X0)

VTK 33V



Main Features

- ♦ Unique 3D X-Y-Z axis anti-vibration design
- ♦ Integrated 3600RPM fan x 2
- ♦ VTK 33V for VTC 3300E, VTC 6000, VTC 6100, VTC 6110

Specifications

Vibration

- ♦ VTC 3300E, VTC 6000, VTC 6100, VTC 6110 (operating)
2G@10~500 Hz with automotive HDD
3G@5~500 Hz random with CF

Thermal

- ♦ 2 x fan (60 x 60mm, 12V) for lowering surface temperature of VTC series

Dimensions

- ♦ 320mm (W) x 180mm (L) x 86.5mm (H)
- ♦ 1.48 Kg (3.3 Lb)

Ordering Information

- ♦ VTK 33V (P/N : 10VK0033V00X0)

VTK 71F



Main Features

- ♦ Integrated 3600RPM fan x 2

Specifications

Thermal

- ♦ 2 x fan (60 x 60mm, 12V) for lowering surface temperature

Dimensions

- ♦ 320mm (W) x 180mm (L) x 86.5mm (H)
- ♦ 1.48 Kg (3.3 Lb)

Ordering Information

- ♦ VTK 71F (P/N : 10VK0071F00X0)