



Main Features

- ◆ 1U rackmount network platform
- ◆ Support 6th/ 7th gen. Intel® Xeon®/ Core™/ Pentium® processors
- ◆ Support DDR4 2400 ECC & REG, up to 32GB
- ◆ Support one LAN module slot
- ◆ Internal two 2.5" HDD bay
- ◆ Single 300 watt PSU

Product Overview

NEXCOM NSA 3170A is a network communication platform based on Intel® Xeon® processor E3-1200 v5/v6 product family. The NSA 3170A is equipped with quad-core computing power, fast DDR4 memory with ECC, and advanced technologies for deliver extra performance boost at a low power envelope for efficient energy use. Also, a maximum of sixteen GbE ports can be implemented through LAN module. The network communication platform NSA 3170A will make either an ideal edge server or a network security appliance in SMB networks.

Specifications

Main Board

- ◆ NSB 3170A
- ◆ Support 6th/ 7th gen. Intel® Xeon®/Core™/Pentium® processors
- ◆ Intel® C236 chipset

Main Memory

- ◆ 2 x DDR4 2400 memory DIMM, support ECC/non-ECC memory, Max 32GB

LAN Features

- ◆ LAN Chip: Intel® i211-AT
- ◆ Support 10/100/1000/10G link speed
- ◆ LAN Bypass: 2 pairs

I/O Interface-Front

- ◆ Power status/HDD status/LAN status/bypass status LEDs
- ◆ 2 x USB 3.0 ports
- ◆ 1 x micro USB console port
- ◆ 1 x RJ45 type console port
- ◆ 8 x copper LAN ports
- ◆ 1 x Reset button
- ◆ 1 x LAN Module Slot

Power Input

- ◆ ATX power supply 300W

I/O Interface-Rear

- ◆ 1 x VGA Port
- ◆ 1 x Power button switch
- ◆ 2 x USB 2.0 ports

Chassis Dimensions

- ◆ Chassis dimension: 438 mm x 300 mm x 44 mm
- ◆ Carton dimension : 544 mm x 506 mm x 205 mm

Weight

- ◆ Without packing: 5.2 KG
- ◆ With packing: 8 KG

Environment

- ◆ Operating temperatures: 0°C~40°C
- ◆ Storage temperature: -20°C~75°C
- ◆ Relative humidity: 10%~90% non-condensing

Certifications

- ◆ CE approval
- ◆ FCC Class A
- ◆ UL

Ordering Information

Barebone

◆ NSA 3170A (P/N: 10S00317001X0)

Intel® C236 PCH, supporting 6th gen. Intel® Xeon®/Core™/Pentium® processors or 7th gen. Intel® Xeon®/Core™ processors, 2 DDR4 memory slots, 8GbE copper LAN ports, SATA DOM, USB ports, VGA port, one PCIe8 LAN expansion slot (front), w/o LCM

Model	P/N Controller	Interface	Type	Port Number	Bypass/Segment	Expansion Slot	Location Slot
NX 140F	10S20140F01X0	XL710-BM1	PCIex8	4 SFP+	None	None	All Slot
NX 142F	10S20142F01X0	XL710-BM1	PCIex8	4 SFP+	2 bypass	None	All Slot
NX 142F-LR	10S20142F03X0	XL710-BM1	PCIex8	4 SFP+	2 bypass	None	All Slot
NX 120F	10S20120F00X0	X710-BM2	PCIex8	2 SFP+	None	None	All Slot
NI 140F	10SK000NI02X0	i350AM4x1	PCIex8	4 SFP	None	None	All Slot
NI 180F	10S10180F01X0	i350AM4x2	PCIex8	8 SFP	None	None	All Slot
NI 142C	10SK000NI03X0	i350AM4x1	PCIex8	4 Copper	2 bypass	None	All Slot
NI 180C	10S10180C01X0	i350AM4x2	PCIex8	8 Copper	None	None	All Slot
NI 184C	10S10184C01X0	i350AM4x2	PCIex8	8 Copper	4 bypass	None	All Slot
NI 142F	10S10142F01X0	i350AM4x1	PCIex8	4 SFP	2 bypass	None	All Slot
NI 121F	10S10121F01X0	i350AM2x1	PCIex8	2 SFP	1 bypass	None	All Slot
NI 140C	10S10140C01X0	i350AM4x1	PCIex8	4 Copper	None	None	All Slot