

NISE 2400-J1900

Intel® Celeron® Processor J1900 Quad Core Fanless System



Main Features

- Onboard Intel® Celeron® Processor J1900 Quad Core, 2.0GHz
- Dual independent display from DVI-I and HDMI®
- 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- 4 x USB 2.0 & 1 x USB 3.0
- 2 x RS-232 & 2 x RS-232/RS-422/RS-485 with auto flow control
- 2 x Mini PCIe socket for optional mSATA/Wi-Fi/4G LTE/3.5G/Fieldbus modules
- Support -5 to 55 degree Celsius extended operating temperature
- Support 9-30V DC input

Product Overview

Powered by Intel® Celeron® Processor J1900 Quad Core, 2.0GHz. Driven by the latest Quad Core Intel® Celeron® Processor, NIE2400-J1900 can provide excellent computing power and is more power-efficient than the platforms based on the previous Generation Intel® Celeron® product family.

NISE2400-J900 supports up to 8G DDR3L memory and have several options on storage devices like CFast, HDD, SSD or mSATA. The NISE2400-J900 comes with 1 x HDMI®, 1 x DVI-I, 2 x GbE LAN ports, 2x COM port with RS-232/422/485 and 5x USB ports including one USB 3.0. NISE2400-J900 supports 9~30V DC input, and can be operated in an extended operating temperature range from -5 to 55 degrees Celsius. This Fanless system supports two mini-PCIe modules, which can be an excellent platform for IOT applications (with optional GbE LAN, Wi-Fi, 3.5G/4G LTE module) and factory automation applications with optional fieldbus module. Its expansion versatility makes NISE2400-J900 a perfect platform for factory automation and M2M intelligent computing applications.

Specifications

CPU Support

- Onboard Intel® Celeron® Processor J1900 Quad Core, 2.0GHz
- Support Intel® Atom™ E3800 processor family from single core E3815, dual core E3825/E3826/E3827 and quad core E3845 with difference SKUs

Main Memory

- 2 x DDR3L 1066/1333 SO-DIMM, supports up to 8GB

Display Option

- Dual independent display
 - HDMI® and DVI-I
 - HDMI® and VGA (via DVI-I connector)

Front I/O Interface

- ATX power on/off switch
- 1 x Power status, 1 x HDD access, 1 x battery low, 4 x programming LEDs, 4 x Tx/Rx LEDs, 2 x LAN LEDs
- 2 x DB9 RS-232 for COM3 & COM4
- 1 x External CFast socket
- 1 x SIM card holder
- 1 x USB 3.0 (900mA per each)
- 1 x Mic in & 1 x Line out
- 2 x Antenna holes for optional Wi-Fi/3.5G antenna

I/O Interface - Rear

- 4 x USB 2.0
- 1 x DVI-I display output
- 1 x HDMI® display output
- 1 x Remote power on/off switch
- 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- 2 x DB9 for COM1 & COM2, both support RS-232/422/485 with auto flow control
 - Jumper-free setting on RS-232/422/485
- 1 x 3-pin DC input, supports +9 to 30VDC input

I/O Interface - Internal

- 4 x GPI and 4 GPO (5V, TTL type)

Storage Device

- 1 x CFast card socket (SATA 2.0)
- 1 x 2.5" HDD space (SATA 2.0)
- 1 x mSATA from mini-PCIe socket if SATA HDD is not installed


Expansion Slot

- 2 x Mini PCIe socket for optional Wi-Fi/4G LTE/3.5G

Power Requirement

- Power input: +9Vdc to +30Vdc
- 1 x Optional 24V, 60W power adapter

Dimension Drawing



Dimensions

- 191mm (W) x 200mm (D) x 60mm (H) without wall-mount bracket

Construction

- Aluminum and metal chassis with fanless design

Environment

- Operating temperature:
Ambient with air flow: -5°C~55°C
(according to IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14)
- Storage temperature: -30°C to 85°C
- Relative humidity: 10%~95% (non-condensing)
- Shock protection:
HDD: 20G, half sine, 11ms, IEC 60068-2-27
CFast: 50G, half sine, 11ms, IEC 60068-2-27
- Vibration protection w/ HDD condition:
Random: 0.5Grms@5~500Hz, IEC 60068-2-64
Sinusoidal: 0.5Grms@5~500Hz, IEC 60068-2-6
- Vibration protection w/ CFast & SSD condition:
Random: 2Grms@5~500Hz, IEC 60068-2-64
Sinusoidal: 2Grms@5~500Hz, IEC 60068-2-6

Certifications

- CE
- FCC Class A

OS Support Lists

- Windows 8, 32-bit/64-bit
- Windows Embedded Standard 8, 32-bit/64-bit
- Windows 7, 32-bit/64-bit
- Windows Embedded Standard 7, 32-bit/64-bit
- Windows 10 IoT Enterprise, 64-bit
- Linux Kernel version 3.8.0

Ordering Information

Barebone

- **NISE 2400-J1900 (P/N:10J00240008XE)**
Onboard Intel® Celeron® Processor J1900 Quad Core, 2.0GHz
- **24V 60W AC/DC power adapter w/o power cord**
(P/N: 7400060024X00)