



Main Features

- Support 35W 10th Gen Intel® Core™ i9/i7/i5/i3/Pentium®/Celeron® processor (Comet Lake-S)
- Stylish slim bezel, metal housing with robust aluminum front zero bezel for harsh environment
- 10 points P-Cap touch with zero bezel flush front design
- 2 x DDR4 2933MHz memory, up to 32GB (non-ECC)
- Dual Intel® GbE LAN ports/DP++/dual USB 3.0
- 1 x RS-232, 1 x RS-232/422/485 with isolation (optional)
- Internal support :
 - 1 x Mini PCIe (PCIe x1, USB 2.0, SATA)
 - 1 x M.2 3042/3052 Key B (PCIe x1, USB 3.0, USB 2.0)
 - 1 x M.2 2242 Key B (USB 2.0, SATA)
- 24VDC input; supports AT/ATX power mode
- 1 x PCIe x4 expansion

Product Overview

The new 15.6" fanless panel PC IPPC 1611-C11 is equipped with a high-performance 10th Gen Intel® Core™ i9/i7/i5/i3 socket-type CPU platform, intended for versatile industrial applications. IPPC 1611-C11 has a narrow border touch screen and a LED backlight LCD panel with 1366 x 768 (HD) resolution. The front panel which adopts a flush, narrow border design and complies with the IP66 standard to make it perfectly fit in industrial applications.

IPPC 1611-C11 contains dual Gigabit Ethernet connectors, one mini-PCIe slot, and an M.2 slot to support multiple networks of LAN/WLAN/WWAN (5G). In addition, it can hook a 2nd display via DP++ for dual independent display, one adjustable RS-232/422/485 port with isolation, and provides a PCIe x4 for add-on card expansion.

Specifications

Panel

- LCD size: 15.6", 16:9
- LCD interface: LVDS
- Resolution: HD 1366 x 768
- Luminance: 400cd/m²
- Viewing angle: 80 (U), 80 (D), 85 (L), 85 (R)
- Backlight: LED

Touch

- Ten points P-Cap (projected capacitive touch)
- Light transmission: 86%
- Interface: USB
- Anti-scratch surface: 6H hardness

System

- CPU support list: 10th Gen Intel® Core™ i processor family, LGA 1200 socket type, max 35W
 - 10th Gen Intel® Core™ i9-10900TE (20M Cache 1.8GHz)
 - 10th Gen Intel® Core™ i7-10700TE (16M Cache 2.0GHz)
 - 10th Gen Intel® Core™ i5-10500TE (12M Cache 2.3GHz)
 - 10th Gen Intel® Core™ i3-10100TE (6M Cache 2.3GHz)
 - 10th Gen Intel® Pentium® G6400TE (4M Cache 3.2GHz)
 - 10th Gen Intel® Celeron® G5900TE (2M Cache 3.0GHz)

- BIOS: AMI BIOS
- Intel® PPT (FPM) support; TPM IC (optional)
- System chipset: Intel® H420E PCH
- System memory: 2 x DDR4 2933 SO-DIMM, non-ECC, supports up to 32GB
- Storage device:
 - 1 x M.2 2242 Key B
 - 1 x Mini PCIe
 - 1 x Hard drive tray

Rear I/O


- 2 x DB9 for COM1&COM2
 - COM1: RS-232
 - COM2: RS-232/422/485 auto flow control (isolation)
- 2 x USB 3.1 port (900mA per each)
- 1 x DP++
- 2 x Intel® I210-IT GbE LAN port; supports WoL, teaming and PXE
- 1 x 2-pin remote power on/off switch
- 24V DC input

Expansion Slot

- One PCIe x4 expansion slot: FHFL, 40W max
- 1 x Mini PCIe for Wi-Fi/mSATA
- 1 x M.2 3042/3052 Key B for 5G/Wi-Fi
- 1 x nano SIM card onboard



Dimension Drawing



Power Requirements

- ♦ AT/ATX power mode (default: ATX power mode)
- ♦ Power input: +24V DC
- ♦ Power adapter: optional AC to DC power adapter (24V DC, 120W)

Dimensions

- ♦ 397mm x 257.1mm x 71.7mm

Construction

- ♦ Support Panel/ Wall / VESA (100x100mm) mount
- ♦ IP65 Rating front panel

Environment

- ♦ Operating temperature:
 - Ambient with air flow: 0°C~50°C
 - Storage temperature: -20°C~75°C
- ♦ Relative humidity: 10%~90% (non-condensing)
- ♦ Shock protection:
 - HDD: 20G, half sine, 11ms, IEC 60068-2-27
 - M.2: 50G, half sine, 11ms, IEC 60068-2-27
- ♦ Vibration protection with SSD&M.2 condition:
 - 2.0Grms@random condition, 5~500Hz, 1hr/axis (M.2/ SSD operating)

Certifications

- ♦ CE approval- EN 61000-6-2- EN 61000-6-4
- ♦ FCC Class A

OS Support

- ♦ Windows 11
- ♦ Windows 10 64bit

Weight Information

- ♦ 7 kg

Ordering Information

Barebone

- ♦ **IPPC 1611-C11 (P/N: 10II0161100X0)**
15.6" TFT HD 16:9 heavy industrial panel PC 10th Gen Intel® Core™ i processor support, P-Cap screen, DDR4, PCIe slot supported

Others

- ♦ **24V, 60W AC/DC power adapter w/o power cord (P/N: 7400060054X00)**
- ♦ **24V, 120W AC/DC power adapter w/o power cord (P/N: 7400120029X00)**