



Main Features

- Onboard Intel® Atom® Processor N97 quad-core 2.0GHz
- 1 x HDMI®
- 3 x 2.5GbE LAN; supports WoL, teaming, PXE, and EtherCAT
- Storage support 2 x M.2 SATA SSD
- 1 x M.2 2230 Key A for Wi-Fi 4/5/6E module
- 1 x M.2 3042/3052 Key B for 4G/5G module
- 6 x USB 3.2
- 2 x DB9 for RS-232/422/485
- Support 12~24V DC input; supports AT/ATX power mode

Product Overview

NISE 50 A04-03 is a fanless PC powered by the latest generation Intel® N97 processor. It delivers power-efficient performance designed for next-generation industrial edge embedded systems that require high-resolution graphics and low power consumption - such as industrial automation, intelligent transportation, retail, and smart city IoT solutions.

NISE 50 A04-03 supports an operating temperature range of -20°C to 60°C, ensuring reliable performance in industrial environments. It features strong connectivity with 3 x 2.5GbE LAN ports and 2 x COM ports, ideal for Modbus TCP and Modbus RTU communication. The system supports scalable networks and flexible storage configurations with 1 x M.2 slot for 5G/LTE, 1 x M.2 slot for Wi-Fi and Bluetooth, and 1 x M.2 slot for storage. It also supports 12V DC/24V DC power input and features onboard TPM 2.0 for enhanced security.

Specifications

Model

- Intel® Processor N97 (embedded), with I/O board

Main Memory

- 1 x DDR5 4800 SO-DIMM, supports up to 16GB (N97) / 32GB (x7433RE)

Display Option

- 1 x HDMI®

LED indicator

- 1 x Battery low Status
- 2 x GPO

I/O Interface - Front

- ATX power on/off switch
- 1 x Intel® I226-IT 2.5GbE TSN LAN ports; supports WoL, teaming, PXE, and EtherCAT
- 2 x Intel® I226-V 2.5GbE LAN ports; supports WoL, teaming, PXE, and EtherCAT
- 2 x USB 3.2
- 1 x HDMI®
- 1 x DB9 for COM1, supports RS-232/422/485 with auto flow control, BIOS setting
- 1 x 3-pin DC input, supports +12/24V DC

I/O Interface - Rear

- 1 x DB9 for COM2, supports RS-232/422/485 with auto flow control, BIOS setting
- 4 x USB 3.2

I/O Interface - Internal

- 1 x nano-SIM holder
- TPM 2.0

Expansion Slot

- 1 x M.2 2230 Key A, supports optional Wi-Fi 4/5/6E module
- 1 x M.2 2242/2280 Key B, supports optional SATA Storage module
- 1 x M.2 2242/3042/3052 Key B socket, supports optional 4G/5G/SATA storage module

Power Requirement

- Power input: +12/24V DC
- Optional 24V, 60W/120W power adapter


Construction

- Aluminum top cover and metal chassis with fanless design

Environment

- Operating temperature: Ambient with air flow(according to IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14): -20°C~60°C

Dimension Drawing



- ♦ Storage temperature: -10°C~80°C
- ♦ Relative humidity: 95% at 40°C
- ♦ Shock protection:
 - M.2: 50G@wall mount, half sine, 11ms(operation) , IEC 60068 2-27
- ♦ Vibration protection w/ M.2 & SSD condition:
 - Random: 2Grms@5~500 Hz, IEC 60068-2-64
 - Sinusoidal: 2Grms@5~500 Hz, IEC 60068-2-6

Dimensions

- ♦ 186mm (W) x 150mm (D) x 28mm (H)

Weight Information

- ♦ 0.9kg

Certifications

- ♦ CE
- ♦ FCC Class A

Support OS

- ♦ Windows 11
- ♦ Windows 10 IoT Enterprise, 64-bit
- ♦ Linux Kernel version 4.1

Ordering Information

- ♦ **NISE50 A04-03 system (P/N: 10J00005063X0)**
Intel Processor N97 2.0GHz, with I/O board
- ♦ 24V, 60W AC to DC power adapter w/o power cord
(P/N: 7400060054X00)
- ♦ 24V, 120W AC to DC power adapter w/o power cord
(P/N: 7400120029X00)