



Main Features

- 10.4" XGA TFT LCD monitor with 5-wire resistive touch
- Aluminum die-casting and fanless design
- Built-in Intel Atom® x5-E3930 processor, 1.8GHz
- Automatic/manual brightness control
- Touch with heater supported
- On screen F1 ~ F10 programmable function keys
- Powered USB and COM (5V/12V, 1.5A) for accessories
- Military standard for vibration and shock
- UPS Battery supported
- iButton and RFID for ID identification
- Wide range DC input from 9V~60V DC in
- Sunlight readable capability: 1,200nits LCD brightness
- Operating system: Windows and Linux
- CE/FCC/EMark

Product Overview

VMC 3020, 10.4-inch all in one robust vehicle mount computer, is designed for the warehouses, logistic and material handling market. It implements the latest Intel Atom® x5-E3930 processor (codename Apollo Lake) and can work on Windows and Linux for different OS. markets. To work well in the special warehouse application, VMC 3020 specially designs powered I/O (up to 12V DC out) to power on printer, scanner... Besides, heater inside VMC 3020 can help forklift resume to work quickly when it stays in snow for a long time. Back-up battery can assist system without stopping working if power battery in forklift suddenly drops down. 1,200 nits brightness is for sunlight readable purpose.

Specifications

LCD Panel

- 10.4-inch TFT LCD panel with LED backlight
- 1024 x 768 pixels (XGA)
- Brightness: 1200 cd/m² (typical)
- Viewing angle: 140° (H):120°(V)
- Contrast ratio: 500:1 (typical)

Touch Screen Sensor

- 5-wire resistant touch
- Anti-glare coating surface
- Transmission rate: 81 ± 3%

CPU & Chipset

- Intel Atom® x5-E3930 processor dual core 1.8GHz

Memory

- One 204-pin DDR3L 1600MHz SO-DIMM slot (Default: 2GB)

Expandable Storage

- 1 x CFast
- 1 x 2.5" SATA SSD bay

Expansion

- 1 x half-size mini-PCIe socket (PCIe + USB) for WLAN option
- 1 x full-size mini-PCIe socket (USB) x 1 for WWAN option
- 1 x M.2 key-E (PCIe + SDIO + UART + USB) for WLAN option
- 1 x SIM slot

I/O Interface-Front

- 5 x on screen display buttons
 - Power on/off
 - Volume control (+/-)
 - Brightness control (+/-)
- Light sensor
- 4 x LED indicators (power/battery charging, WLAN, shift, storage)
- F1 ~ F10 programmable function keys
- 2 x Built-in 2W speakers


I/O Interface-Lateral

- Right Side:
 - 1 x CFast card slot
 - System reset button
 - USB 2.0 host type A connector
- Left Side:
 - 1 x antenna for WWAN

I/O Interface-Bottom

- 1 x Power Switch (ATX mode)
- Lockable power connector (power, ignition, ground)
- 2 x RS232 (full signals, RI, 0V, 5V/1.5A, 12V/1.5A)
- 1 x DB15
 - 1 x Isolated CAN 2.0B
 - 1 x iButton

Dimension Drawing



- 1 x RFID (12V/1A, 5V/1A, 4pin)
- 1 x Optional RS232 Tx/Rx (share with GPS UART)
- 2 x GPI
 - Sink type: 5VDC TTL (default)
 - Source type: 3 ~ 28VDC
- 2 x GPO
 - Sink type: 5VDC TTL (default), max current: 20mA
 - Source type: 3 ~ 28VDC, max current: 150mA
- 1 x Powered USB (5V/1.5A, 12V/1.5A)
- 1 x USB Type A (5V/1A)
- 1 x Mic-in, 1 x Line-out
- 1 x Antenna for GPS

I/O Interface-Top

- 2 x Antenna for Wi-Fi

Mechanical

- Cooling system: Fanless
- Enclosure: Aluminum die castig
- Mounting: VESA 75/100 & desktop mounting
- Ingress protection: front panel IP65
- Dimension: 289.98mm (W) x 229.97mm (H) x 77.95mm (D), including battery
- Weight: 3kg, 6.61lb

Power Management

- 9V~60V DC in (UPS: 12V, 24V, 36V and 48V)
- Reverse protection/over voltage protection/under voltage protection
- Ignition On/Off control & programmable On/Off delay timing
- Wake up by SMS, RTC and ignition

Operating System

- ♦ Windows 10
- ♦ Linux: YOCTO (by request)

Environment

- ♦ Operating temperatures: Ambient with air -30°C to 60°C
- ♦ Storage temperatures: -30°C to 70°C
- ♦ Relative humidity: 10% to 90% (non-condensing)
- ♦ Vibration
 - Operating: MIL-STD-810G, 514.6 Procedure 1, Category 4
 - Storage: MIL-STD-810G, 514.6 Procedure 1, Category 24
- ♦ Shock
 - Operating: MIL-STD-810G, Method 516.6, Procedure I, trucks and semi-trailers= 20g
 - Crash hazard: MIL-STD-810G, Method 516.6, Procedure V, ground equipment= 75g

Standards/Certifications

- ♦ CE/FCC class B/E13

Ordering Information

- ♦ **VMC 3020 (P/N: 10VC0320000X0)**
10.4" Rugged Vehicle Mount Computer with Intel Atom® x5-E3930, Touch Screen and Front IP65 w/o Heater