

NEX 604

Mini-ITX, Intel® Atom™ Dual-Core D2700 2.13GHz, 2x DDR3,
VGA/ LVDS/ HDMI, 2x GbE, 2x SATA, 4x COM, 6x USB, 2x mPCIe, PCI



Main Features

- Intel® Atom™ Dual-Core D2700/ 2.13GHz processor
- Intel® NM10 Express chipset
- Dual 204-pins DDR3 SO-DIMMs support max. 4GB SDRAM memory
- Support VGA/HDMI, VGA/LVDS or HDMI/LVDS dual displays
- 6x USB, 4x COM, 2x GbE, 2x SATA, 1x LPT
- Audio Mic-in/ Line- out, (internal Line-in)
- 2x Mini-PCIe (1x full/SIM tray, 1x half-size), 1x PCI
- Single DC +12V input by AT/ ATX mode

Product Overview

NEX 604 is a Mini-ITX industrial MB embedded Intel® Atom™ D2700 2.13GHz dual-core processor, which integrated Intel® HD graphic controller SGX545 to support 640MHz/ DX9 NEX 604 supports VGA, LVDS (1x ch. 24-bit up to 1440x 900 @ 60Hz) and HDMI (1080p) by dual displays interface as standard along with two DDR3 SO-DIMMs for max 4GB memory.

NEX 604 is equipped with Intel® NM10 Express chipset to provide two SATA 2.0 for SSD, six USB 2.0 (2x USB to 2x mPCIe slots), two GbE by Realtek RTL8111E PCIe LAN controllers, two Mini-PCIe slots for one support full-size card with SIM tray and one half-size slot for standard add-on I/O application. The HDMI and full I/O function supports make NEX 604 well fit for data logging, mobile communication, networking, gateway and embedded focus applications.

Specifications

Embedded Support

- Intel® Atom™ processor D2700 2.13GHz CPU

Main Memory

- Dual 204-pin SO-DIMMs support DDR3 up to 4GB SDRAM 800/1066MHz

Chipset

- Intel® NM10 Express chipset

BIOS

- AMI BIOS
- Plug & Play support
- Advanced power management
- Advanced configuration & power interface
- 16M bits SPI ROM

On-board LAN

- 2x Realtek 8111E PCI Express Gigabit Ethernet
- Support boot from LAN (PXE)
- 2x RJ45 with LEDs built-in 2x dual stackable USB type A connectors on edge I/O

Display

- New 2-chips solution 32nm package Intel® Atom™ processor D2700 integrated 3D graphics engine SGX545, to support up to 640MHz/

DX9, and provides multi-options for high-resolution displays

- Analog VGA interface:
1x VGA by DB15 connector
Resolution up to 1920x 1200 75Hz
- HDMI interface:
1x HDMI connector
Resolution up to 1920x1200
- LVDS interface:
• Single (24-bit) LVDS panel, resolution up to 1440x 900 by DF13 20-pin LVDS connector
- Inverter (LVDS panel backlight) interface:
1x 7-pins CCFL for LCD panel backlight inverter
- Audio:
Realtek ALC886-GR High Definition codec
1 x Mic-in/ 1 x Line-out by audio jack on edge I/O and 1x Line-in by internal 4-pins header
- Expansions:
2 x Mini-PCIe (1x full-size/ SIM tray and 1x half-size slots)
1 x PCI slot (32bit/ 33Mhz)

I/O Interfaces- Front

- Serial port: 4 ports
COM1, RS232 by DB-9 male on edge I/O
COM2, 3, 4 ports support 3x RS232 by three 2x 5-pins box-headers

The diagram illustrates the system architecture centered around the Cedarview-D Microprocessor, which includes DDR3 Memory Controller and DDR3 ChA. The processor is connected to various components:

- Memory:** SODIMM - A and SODIMM - B via DDR3-1066.
- Display:** HDMI, VGA, and LVDS5 (SC LVDS 24 bpps) via DMI.
- Storage:** SATA 0 and SATA 1 via SATA (2) interface.
- Connectivity:**
 - USB 2.0 (8) to BACK I/O (0,1, 2,3, 4,5, 6,7) and TO MINI CARD.
 - PCI-E *1 (4) to LAN CONTROLLER (REALTEK:RTL8111E-VL-CG) and MINI CARD A/B.
 - PCI to PCI SLOT.
 - COM1-4, LPT, KB/MS, IR, and H/W MONITOR via SUPPER I/O IT8783F/AX-L.
- Audio:** HD AUDIO ALC886-GR connected to LINE-OUT, MIC-IN, and LINE-IN.
- Other:** SPI to PCT25VF016B and DMI x4 2.5Gb/s to INTEL NM10.

- Mini-ITX, embedded Intel® Atom™ Dual-Core D2700/ NM10, 2x DDR3, VGA/ LVDS/ HDMI, 2GbE, 2SATA, 4COM, 6USB, 2mPCIe, PCI and DC+12V input