



Main Features

- 1U workstation rack mount system
- Intel® Xeon® (Skylake-S)/Core™/Pentium® processor
- Support DDR4 2400
- Four LAN module slots
- Support LCM module (optional)

Product Overview

NEXCOM network appliance NSA 5170C helps small and medium-sized businesses (SMBs) scrutinize network traffic with ease. Featuring Intel® Xeon® product family, the NSA 5170C delivers scalable computing performance, high port density, and easy expansions of high-speed networking interface. By simplifying deployment, configuration, and management of network security controls, NEXCOM network appliance can fend off unauthorized access, patch potential security loopholes, and create protected networks for business environments.

Specifications

Main Board

- NSB 5170C
- Intel® Xeon® (Skylake-S)/Core™/Pentium® processors
- Intel® C236

Main Memory

- 4 x DDR4 2133/2400 DIMM support ECC/non-ECC memory, max. 64GB

LAN Features

- Swappable LAN modules
- LAN bypass
- * Please see LAN module list information

I/O Interface-Front

- Power status/HDD status/2 x GPIO status LEDs
- 1 x Management ports (LAN chip: Intel® i210)
- 2 x USB 2.0 ports
- 1 x RJ45 type console port
- 1 x Reset button
- 4 x PCIe 3.0 LAN module slots (x8, x8, x4, x4)

I/O Interface-Rear

- 1 x VGA port
- 1 x Power button switch
- 2 x USB 2.0 port

Storage Device

- 1 x CF card
- 1 x 2.5" HDD bay

Power Input

- Power supply 300W (1+1) redundant PSU

Dimensions

- Chassis dimension: 438 mm x 470 mm x 44 mm
- Carton dimension: 665 mm x 547 mm x 226 mm

Weight

- Without packing: 7.5 kg
- With packing: 10.5 kg

Certifications

- CE Approval
- FCC Class A
- UL

Ordering Information

Barebone

♦ **NSA 5170C (P/N: 10S00517002X0)**

Supports Intel® Xeon®(Skylake-S)/Core™/Pentium® processors, 4 x DDR4, 2 x PCIe x8 LAN and 2 x PCIe x4 LAN expansion slot (front), w/ o LCM

Model	P/N Controller	Interface	Type	Port Number	Bypass/Segment	Expansion Slot	Location Slot
NX 140F	10S20140F01X0	XL710-BM1	PCIe x8	4 SFP+	None	None	1,2
NX 120F	10S20120F00X0	X710-BM2	PCIe x8	2 SFP+	None	None	1,2
NI 140F	10SK000NI02X0	I350-AM4x1	PCIe x8	4 SFP	None	None	All Slot
NI 180F	10S10180F01X0	I350-AM4x2	PCIe x8	8 SFP	None	None	2
NI 180C	10S10180C01X0	I350-AM4x2	PCIe x8	8 Copper	None	None	2
NI 140C	10S10140C01X0	I350-AM4x1	PCIe x8	4 Copper	None	None	All Slot

