# VTC 7280-7C5/-5C5

Fanless AI Powered Vehicle Computer with Intel® Core™ Ultra Meteor-Lake H





# **Main Features**

- Powered by Intel<sup>®</sup> Core<sup>™</sup> Ultra Meteor-Lake H, up to 26 TOPS AI computing power
- Fanless, compact and rugged design
- 5 x 2.5GbE, up to PoE++ (IEEE 802.3bt) support
- Supports 100/1000Base-T1 Automotive Ethernet (optional)
- Expandable to 2x WWAN and 2x WLAN for enhanced mobile router performance
- 2 x 2.5" SSD, 1 x NVMe SSD (PCIe 4.0 x4) for data integrity
- 9~36V DC-IN with ignition control & OCP/OVP
- Wide range operating temperature of -40°C~60°C
- MIL-STD Military standard for anti-vibration/shock
- CE/FCC, UKCA, E mark certified

# **Product Overview**

Powered by the Intel<sup>®</sup> Core<sup>™</sup> Ultra Meteor Lake H processor with 26 TOPS of AI computing power, the VTC 7280-xC5 offers a 30% performance boost over its predecessor. Its compact, rugged, and fanless design enables installation in space-constrained environments and operation in harsh conditions. It is suitable for various in-vehicle applications, including fleet management, logistics/AMR, ITS, construction, ANPR, and public transportation security surveillance.

Equipped with a range of peripherals, including 5 2.5GbE PoE++, 1/3 USB 3.2/2.0, 2 isolated CAN FD, 3 serial ports, NVMe/2.5" SSD, 4 x nano-SIM slot, two HDMI®, and a wide-range 9~36V DC/IGN control, the VTC 7280-xC5 is a sophisticated AI-aided telematics computer. As an edge AI computer, it supports multi-LTE/5G and Wi-Fi 5/6 for cloud SaaS to provide AIoT/AI training/inference services.

Designed to withstand harsh environments, the VTC 7280-xC5 operates at temperatures ranging from -40°C to 60°C and complies with the MIL-STD-810H military standard for vibration and shock resistance. The VTC 7280-xC5 is certified to meet global standards, including CE/FCC Class A, UKCA, and E mark (E13).

# **Specifications**

# CPU

- Intel<sup>®</sup> Core<sup>™</sup> Ultra Meteor-Lake H
- Core<sup>™</sup> Ultra 7 processor 155H
- Core™ Ultra 5 processor 125H
   NPU
- 2 x 2048 MACs computing performance
- Graphics
- Intel<sup>®</sup> Arc<sup>™</sup> graphics
- Max resolution: 4096x2160@60Hz (HDMI<sup>®</sup>)
  DirectX: 12.2, OpenGL: 4.6

## - DirectX: 12.2

Memory

2 x DDR5 5600 SO-DIMM, 8GB defualt, up to 32G per DIMM

## Storage

- 2 x 2.5" SATA 3.0 SSD (15mm height, removable)
- 1 x M.2 2280 Key M SSD (PCIe 4.0 x4), Hailo card in option

## **Expansion Slots**

- 1 x Mini PCIe slot (PCIe 4.0, USB 2.0)
- 1 x Mini PCIe slot (PCIe 4.0, USB 2.0), BOM option for M.2 Key B (USB 3.2/2.0), supports nano-SIMs
- 1 x M.2 Key B 3042/3052 (USB 3.2/2.0), supports nano-SIMs for LTE/5G module
- 1 x M.2 Key E 2230 (PCle 4.0 x2 & USB 2.0)

# Display

- 1 x HDMI<sup>®</sup> 2.0a, up to 3840x2160@60Hz
- 1 x VGA, up to 1920x1200@60Hz

# Security

TPM 2.0 - Infineon SLB9672VU2.0FW15.23

# 2.5GbE PoE++

- 5 x independent 2.5GbE RJ45 PoE port
  - iAMT/ WoL/ PXE support (LAN1)
  - 9Kbyte Jumbo frame
  - IEEE 802.3af/at/bt, total 80W, PSE 60W for LAN1
  - PTP (IEEE 1588) support
  - Controller: Intel® I226-IT

# Audio

- 1 x Line out, unbalanced stereo, left/right channel, audio Jack
- 1 x MIC in, stereo, audio Jack
- 1 x Line in, wafer reserved
  Codec: Realtek ALC888S-VD2-GR

# DC Out

# 12V DC/3A, terminal block

- USB
  - 1 x USB 3.2 Gen 2
  - Host Type-A
  - 5V@900mA
    - Up to 10Gbit/s link speed & compliance with USB 2.0 (LS/FS/HS link
  - speed) 3 x USB 2.0
  - Host Type-A
  - 5V@500mA each

## Serial Port

- 2 x COM port (DB9), supports full RS-232/422/485
- 1 x COM port (DB9), supports full RS-232 (DB9)
- 1 x full RS-232 (wafer reserved)
- RS-232 working voltage, +- 9V, baud rate up to 115.2kb/s
- 2-wire/4-wire RS-485 (Baud rate: 300~115.2Kbps)





# **MEMS Sensor**

3D accelerometer and 3D gyroscope, ST LSM6DSLTR

### DI/DO (isolation)

- 4-bit input
  - Source: 9~36V DC (12V@0.6mA/24V@1.2mA)
  - External: 0~33V DC pull-high, high/low level 3.3 33/ 0 2V DC
- 4-bit output
- Source: 9~36V DC (nominal 35mA@24V)
- External: 5~36V DC pull-high, sink current w/ 220mA for each bit, 500mA max (@25C)
- Source or external can be selected by DIP S/W (default: source type)

## CAN Bus

- 2 x CAN FD, compatible with CAN 2.0A/2.0B
- Up to 5Mb/s in data transmit, 2.5KV isolated
- IEC 61000-4-2 Electrostatic Discharge (ESD): ± 6KV/8KV (contact/air) GNSS
- u-blox NEO-M9N GNSS module (VIOB-GPS-07) for GPS/Gloness/
- QZSS/Galileo/Beidou Optional DR (Dead Reckoning) function, NEO-M9V (VIOB-GPS-DR07)

# Power Supply

- Nominal voltage: DC 9V to 36V
  Cranking voltage: DC 6V to 9V (less than 20 sec)
- Reverse protection, OCP & UVP (shut down once exceeding 36.5V) Ignition on/off control & programmable on/off delay timer
- Optional for remote power on/off control

#### I/O ports, Front-Plate ATX power & Reset button

- 8 x LED Indicator
- 4 x nano-SIM slot (SIM1-1, SIM1-2, SIM2-1, SIM2-2)

- 1 x USB 3.2, Type-A
   3 x USB 2.0, Type-A
   1 x HDMI®, 1 x VGA
   2 x removable 2.5" SSD bay
- 1 x PR-SMA for GNSS

### I/O ports, Rear-Plate

- 1 x RS-232 (DB9, COM3)
- 2 x RS-232/422/485 (DB9, COM1, COM2)
- Audio jack for Line out, MIC in
- Multi-port DB15 (4 x DÍ, 4 x DO, 2 x CAN FD)
  5 x 2.5GbE PoE, RJ45
  1 x terminal block (DC-OUT)

- 3-pin Phoenix for 9~36V DC-in
- 2 x PR-SMA for Wi-Fi ant. 4 x SMA for LTE/5G ant.

### Internal Heater

- Activation threshold: less than -25°C
- Remote heater ON/OFF signal, wafer reserved

#### **Dimensions & Weight**

- 260.0mm x 180.0mm x 66.5mm (w/o mount bracket) ٠
- . 280.0mm x 180.0mm x 72.5mm (w/ mount bracket)
- Weight: 5.8kg

#### Environment

- Operating temperatures: -40°C~60°C (45W CPU w/ PoE, fanless)
- Storage temperatures: -40°C~85°C
- Relative humidity: 10%~95% (non-condensing)

#### Vibration & Shock

- Vibration in operating
- MIL-STD-810H, 514.8C Procedure 6, Category 4
- IEC 60068-2-64: 2.0g@5~500Hz
- Vibration in storage
- MIL-STD-810H, 514.8E Procedure 1, Category 24, 7.7g
- Shock
- MIL-STD-810H, 516.8 Procedure I, trucks and semi-trailers=40g Crash hazard: Procedure V, ground equipment=75g

#### Certifications

- CE approval, FCC Class A, UKCA, E mark certified
- **Operating System**

# • Windows 11

- Windows 10 64-bit,
- Windows 10 IOT Enterprise 64-bit
- Linux (Ubuntu 22.04, Linux 5.19)

# Ordering Information

- VTC7280-7C5 (P/N: 10V00728000X0) Intel® Meteor Lake H (155H), 5 x 2.5GbE PoE++, 1x USB 3.2, 3x USB
- 2.0, 3 x Serial, 2 x 2.5"SSD, 4DI/4DO, 2 x CAN FD, 9~36V DC/IGN
- VTC7280-5C5 (P/N: 10V00728001X0) Intel® Meteor Lake H (125H), 5 x 2.5GbE PoE++, 1 x USB 3.2, 3 x USB 2.0, 3 x Serial, 2 x 2.5"SSD, 4DI/4DO, 2 x CAN FD, 9~36V DC/IGN