

IWF 501/501D

IP55 Outdoor AP/CPE Single Radio Dual Band, 802.11b/g/n



Main Features

- ♦ AP/Client/Bridge/Router mode supported
- ♦ Compliant with IEEE 802.11 b/g/n 2x2 MIMO
- ♦ 300 Mbps data rate
- ♦ 24VDC PoE input
- ♦ Fast Ethernet RJ45
- ♦ WEP, WPA, WPA2
- ♦ Operating temperature range from -35 to 75°C
- ♦ FCC/CE certification

Product Overview

IWF 501series are cost effective 802.11b/g/n outdoor AP/CPE operating in 2.4GHz band. It has a build-in dual-polarity antenna or detachable SMA connectors with dual Ethernet ports. The IWF 501 series support passive 24VDC PoE allowing easy installation without any environment limitation.

IWF 501 Series Category

Model	Description	Antenna
IWF 501	Outdoor AP/CPE 2.4GHz 802.11 b/g/n 2x2	12dBi embedded antenna
IWF 501D	Outdoor AP/CPE 2.4GHz 802.11 b/g/n 2x2	2 x SMA connectors

Specifications

Wireless Radio

- ♦ 2 x 2 MIMO radios

Frequency Ranges

- ♦ USA: 2.412 ~ 2.462 GHz
- ♦ Europe: 2.412 ~ 2.472 GHz
- ♦ Japan: 2.412 ~ 2.484 GHz
- ♦ China: 2.412 ~ 2.472 GHz

RF Output Power: (± 2dBm)

- ♦ IEEE802.11b
 - 27± 2dBm@1M
 - 27±2dBm@11M
- ♦ IEEE802.11g
 - 27± 2dBm@6M
 - 23± 2dBm@54M
- ♦ IEEE802.11g/n HT20
 - 27± 2dBm@MCS0/8
 - 22± 2dBm@MCS7/15
- ♦ IEEE802.11g/n HT40
 - 27± 2dBm@MCS0/8
 - 22± 2dBm@MCS7/15

Receive Sensitivity

- ♦ IEEE802.11b
 - -95dBm@1M
 - -90dBm@11M
- ♦ IEEE802.11g
 - -90 dBm@6M
 - -75 dBm@54M
- ♦ IEEE802.11g/n HT20
 - -91 dBm@MCS0/8
 - -72 dBm@MCS7/15
- ♦ IEEE802.11g/n HT40
 - -88 dBm@MCS0/8
 - -69dBm@MCS7/15

Ethernet

- ♦ 10/100Base-TX MDI/MDI-X RJ-45 x 2

Security

- ♦ Hide SSID
- ♦ MAC Filtering ACL
- ♦ WEP
- ♦ WPA/WPA2

Management

- HTTP(s) Web GUI
- Firmware upgrade
- Configuration Backup and Restore
- Factory default configuration
- SNMP V1/V2c

Utility

- Wireless Site survey
- System Status
- Link Information
- Bandwidth Control
- Distance Adjustment
- Adjustable output power

Physical and Power

- Support 24Vdc Power over Ethernet
- Dimension: 280 x 90 x 47 mm
- Weight: 342g
- Outdoor IP55 rated

Environment Protection

- Operating temperature: -35°C to 75°C
- Storage temperature: -35°C to 75°C
- Humidity: 0% to 95% maximum (Non-condensing)
- Vibration: Random 0.3g

Certification

- FCC
- CE
- RoHS compliant

Package Contents

- IWF 501 series x 1
- 24VDC PoE injector x 1
- Power cord x 1

Ordering Information

- IWF 501-US (P/N: 10T00050101X0)
- IWF 501D-US (P/N: 10T00050103X0)

Applications

