



Main Features

- ◆ 1U rackmount network appliance
- ◆ Support 6th/7th Gen Intel® Xeon®/Core™/Pentium® processor
- ◆ Support DDR4 2400 ECC & non-ECC UDIMM, up to 32GB
- ◆ Support one LAN module slot
- ◆ Internal 2 x 2.5" HDD bay (optional)
- ◆ Single 300 watt PSU

Product Overview

NEXCOM NSA 3170A is a network communication appliance based on Intel® Xeon® processor E3-1200 v5/ v6 product family. The NSA 3170A is equipped with quad-core computing power, fast DDR4 memory with ECC, and advanced technologies for deliver extra performance boost at a low power envelope for efficient energy use. Also, a maximum of sixteen GbE ports can be implemented through LAN module. The network communication appliance NSA 3170A will make either an ideal edge server or a network security appliance in SMB networks.

Specifications

Main Board

- ◆ NSB 3170A
- ◆ Support 6th/7th Gen Intel® Xeon®/Core™/Pentium® processor
- ◆ Intel® C236 chipset

Main Memory

- ◆ 2 x DDR4 2400 UDIMM, support ECC/non-ECC memory, up to 32GB

Storage

- ◆ SATA DOM
- ◆ Internal 2 x 2.5" HDD bay (optional)

LAN Features

- ◆ LAN chip: Intel® i210-AT
- ◆ Support 10/100/1000/10G link speed
- ◆ LAN bypass: 2-pair

I/O Interface-Front

- ◆ Power/HDD/LAN/bypass LED
- ◆ 2 x USB 3.2 port
- ◆ 1 x Micro USB console port
- ◆ 1 x RJ45 type console port
- ◆ 8 x Copper LAN port
- ◆ 1 x Reset button
- ◆ 1 x LAN module slot

Power Input

- ◆ Single power supply 300W

I/O Interface-Rear

- ◆ 1 x VGA port
- ◆ 1 x Power button switch
- ◆ 2 x USB 2.0 port

Chassis Dimensions

- ◆ Chassis dimension: 438 mm x 300 mm x 44 mm
- ◆ Carton dimension : 544 mm x 506 mm x 205 mm

Weight

- ◆ Without packing: 5.2 kg
- ◆ With packing: 8 kg

Environment

- ◆ Operating temperatures: 0°C~40°C
- ◆ Storage temperature: -20°C~75°C
- ◆ Relative humidity: 10%~90% non-condensing

Certifications

- ◆ CE approval
- ◆ FCC Class A
- ◆ UL

Ordering Information

Barebone

♦ NSA 3170A (P/N: 10S00317001X0)

Intel® C236 PCH, supporting 6th Gen Intel® Xeon®/ Core™/ Pentium® processor or 7th Gen Intel® Xeon®/ Core™ processor, 2 DDR4 memory slot, 8GbE copper LAN ports, SATA DOM, USB ports, VGA port, one PCIe x8 LAN expansion slot (front), w/o LCM

Model	P/N Controller	Interface	Type	Port Number	Bypass/Segment	Expansion Slot	Location Slot
NX 140F	10S20140F01X0	XL710-BM1	PCIe x8	4 SFP+	None	None	All Slot
NX 120F	10S20120F00X0	X710-BM2	PCIe x8	2 SFP+	None	None	All Slot
NI 140F	10SK000NI02X0	I350-AM4x1	PCIe x8	4 SFP	None	None	All Slot
NI 180F	10S10180F01X0	I350-AM4x2	PCIe x8	8 SFP	None	None	All Slot
NI 180C	10S10180C01X0	I350-AM4x2	PCIe x8	8 Copper	None	None	All Slot
NI 140C	10S10140C01X0	I350-AM4x1	PCIe x8	4 Copper	None	None	All Slot